



EU1000i

EU1000i Features & Benefits

- Honda Overhead Valve Engine
- Lightweight and Compact
- High Quality, Stable and High Power Output
- Quiet Operation
- Low Fuel Consumption
- Parallel Operation Capability
- Oil Alert®
- Electronic Ignition
- Simultaneous AC/DC use
- Electronic Circuit Breakers
- Inverter (Computer Friendly)
- One Switch for Engine/Fuel Valve On/Off
- USDA-Qualified Spark Arrestor/Muffler
- Fully Enclosed for Quieter Operation
- Eco Throttle™(load dependent operation)
- 2 Year Residential Warranty
- 1 Year Commercial Warranty

EU1000i Specifications

Engine	1.8 HP, Single Cylinder, Overhead Valve, Air Cooled
Displacement	50 cc
AC Output	120V 1000W max.(8.3A) 900W rated (7.5A)
Receptacles	15A 125V Duplex NEMA Plug Number: 5-15P
DC Output	12V, 96W (8A)
Starting System	Recoil
Fuel Tank Capacity	0.6 gallons
Run Time on One Tankful	3.8 hrs. @ rated load 8.3 hrs. @ 1/4 load
Dimensions (L x W x H)	17.7" x 9.4" x 15.0"
Noise Level	59 dB @ rated load 53 dB @ 1/4 load
Dry Weight	29 lbs.